



IP-40AI2A-355

4MP PAN TILT WIFI INDOOR CLOUD CAMERA

4MP PAN TILT WIFI INDOOR CLOUD CAMERA



Model	IP-40AI2A-355	
Model	Name	4MP Pan and Tilt WiFi Indoor Cloud Camera
Camera	Material	Plastic housing
	Sensor	3MP 1/3 CMOS
	Minimal illumination	0.01Lux @(F1.4,AGC ON) ,0 Lux with IR ;
	Shutter	Adaption
	Lens	3.6mm
	Angel	Panning angle: 0~355°, Tilting angle: 0~120°
	Day and night	Automatic switching,ICR infrared filter type
	Infrared distance	10 Meters
	DNR	2D/3D DNR
	WDR	D-WDR
	Video compression	H.265
	H.264 code type	Main Profile
Compression standard	Video compression code rate	Adaptive Bit-rate
	Audio compression	AAC
	Aideo compression code rate	Adaptive Bit-rate



IP-40AI2A-355

4MP PAN TILT WIFI INDOOR CLOUD CAMERA

Model	IP-40AI2A-355	
Image	Max. Resolution	HD:2304x1296 SD:640x360
	FPS	15fps, Network transmission frame rate adaptation
	Image setting	Mirror,flip
	BLC	Support
Network function	Intelligent alarming	Input:Humanoid detection ,humanoid tracking ,humanoid tracking amplification; Output:Linked custom audio
	Configuration	SmartConfig,AP configuration,Manually add
	Port agreement	Cloud privacy agreement
	General function	Anti flicke,double stream,mirror,password protection,watermark
Port	Storage interface	Micro SD card(maximum128G)
	Power interface	Micro USB
	Wired interface	N/A
Wireless parameters	Wireless standard	IEEE802.11b, 802.11g, 802.11n
	Frequency	2.4 GHz ~ 2.4835 GHz
	Channel bandwidth	Support 20MHz
	Safety	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Cloud service	Transmission rate	11b:11Mbps, 11g : 54Mbps, 11n : 150Mbps
	Cloud Service	www.yunyis.com
	APP	Neye3C
	Cloud storage	Additional payment
General	Operating Conditions	-10 °C ~ 45 °C, humidity less than 95% (non-condensing)
	Power supply	DC5V±10%
	Power consumption	5W MAX